

Surveillance System



Indoor Security Cameras



GW713C

Color Dome Security Camera (GW713C)

- Color
- 1/4" COMS CCD
- 3.6mm Lens
- 30PCS infrared LED
- Analog
- 500 TV lines
- 1 Lux
- 82 ft IR Distance



GW721B

Color Dome Security Camera (GW721B)

- Color
- 1/4" Sharp CCD
- 3.6mm Lens
- 26PCS infrared LED
- Analog
- 420 TV lines
- 0 Lux
- 82 ft IR Distance



GW721W

Color Dome Security Camera (GW721W)

- Color
- 1/4" Sharp CCD
- 3.6mm Lens
- 24PCS infrared LED
- Analog
- 420 TV lines
- 0 Lux
- 65.6 ft IR Distance



GW722DR

Color Dome Security Camera (GW722DR)

- Color
- 1/4" Sharp CCD
- 3.6mm Lens
- 24PCS infrared LED
- Analog
- 420 TV lines
- 0 Lux
- 65.6 ft IR Distance



GW714C

Color Dome Security Camera (GW714C)

- Color
- 1/3" COMS CCD
- 3.6mm Lens
- 24PCS infrared LED
- Analog
- 600 TV lines
- 0.1 Lux
- 65.6 ft IR Distance



GW729

Color Dome Security Camera (GW729)

- Color
- 1/3" Sony CCD
- 3.6mm Lens
- 24PCS infrared LED
- Analog
- 420 TV lines
- 0 Lux
- 65.6 ft IR Distance



GW726B

Color Dome Security Camera (GW726B)

- Color
- 1/3" LG CCD
- 3.6mm Lens
- 23PCS infrared LED
- Aluminum
- 520 TV lines
- 0 Lux
- 65.6 ft IR Distance



GW726W

Color Dome Security Camera (GW726W)

- Color
- 1/3" LG CCD
- 3.6mm Lens
- 23PCS infrared LED
- Aluminum
- 520 TV lines
- 0 Lux
- 65.6 ft IR Distance

Indoor Security Cameras



GW728HB

Color Dome Security Camera (GW728HB)

- Color
- 1/3" SONY CCD
- 3.6mm Lens
- 23PCS infrared LED
- Analog
- 520 TV
- 0 Lux
- 65.6 ft IR Distance



GW728W

Color Dome Security Camera (GW728W)

- Color
- 1/3" SONY CCD
- 3.6mm Lens
- 23PCS infrared LED
- Analog
- 520 TV lines
- 0 Lux
- 65.6 ft IR Distance



GW730L

Color Dome Security Camera (GW730L)

- Color
- 1/3" SONY CCD
- 3.6mm Lens
- 24PCS infrared LED
- Analog
- 560 TV lines
- 0.001 Lux
- 65.6 ft IR Distance



GW301H

Color Dome Security Camera (GW301H)

- Color
- 1/3" SONY CCD
- 3.6mm Lens
- 26PCS infrared LED
- Analog
- 560 TV lines
- 0 Lux
- 65.6 ft IR Distance



GW103M

Color Dome Security Camera (GW103M)

- Color
- 1/3" SONY CCD
- Vari-Focal 4~9mm Lens
- 36PCS infrared LED
- Analog
- 480 TV lines
- 0 Lux
- 98.5 ft IR Distance



GW731L

Color Dome Security Camera (GW731)

- Color
- 1/3" SONY CCD
- 3.6mm Lens
- 36PCS infrared LED
- Analog
- 560 TV lines
- 0 Lux
- 98.5 ft IR Distance



GW106H

Color WDR Dome Security Camera (GW106H)

- Color
- 1/3" SONY CCD
- 3.6mm Lens
- 24PCS infrared LED
- Wide Dynamic Range
- 600 TV lines
- 0 Lux
- 65.6 ft IR Distance



GW-BC7

Small Color Security Camera (GW-BC7)

- Color
- 1/3" SONY CCD
- 3.6mm Lens
- Dimension: 38 x 105mm
- Analog
- 540TV lines
- 0.5Lux

Indoor Security Cameras



Color WDR Dome Security Camera (GW726WD)

- Color
- 1/3" SONY CCD
- 3.6mm Lens
- 24PCS infrared LED
- Wide Dynamic Range
- 600 TV lines
- 0 Lux
- 65.6 feet IR Distance



Color Dome Security Camera (GW105H)

- Color
- 1/3" SONY CCD
- Vari-Focal 2.8~10mm Lens
- 98.5 feet IR Distance
- Analog
- 560 TV lines
- 0.001 Lux



Color WDR Dome Security Camera (GW106M)

- Color
- 1/3" SONY CCD
- Vari-Focal 3.5~8mm Lens
- 36PCS infrared LED
- Wide Dynamic Range
- 600 TV lines
- 0 Lux
- 98.5 feet IR Distance



Color Effio-E Dome Security Camera (GW727W)

- Color
- 1/3" Exview HAD CCD II
- 3.6mm Lens
- 24PCS infrared LED
- OSD/2D-DNR/BLC/MD
- 700 TV lines
- 0 Lux
- 65.6 ft IR Distance



Color Effio-E Dome Security Camera (GW727WD)

- Color
- 1/3" Exview HAD CCD II
- Vari-Focal 2.8~12mm Lens
- 22PCS infrared LED
- OSD/2D-DNR/BLC/MD
- 700 TV lines
- 0 Lux
- 59 ft IR Distance



Color WDR Dome Security Camera (GW107WD)

- Color
- 1/3" SONY CCD
- Vari-Focal 2.8~10mm Lens
- 36PCS infrared LED
- Wide Dynamic Range
- 700 TV lines
- 0.001 Lux
- 98.5 feet IR Distance



Color SONY CCD 27X ZOOM Security Camera (GW27XZ)

- Color
- SONY CCD 27X ZOOM
- 3.2mm ~ 86.4mm Lens
- OSD Menu/line control/RS-485 control
- Auto focus
- Analog
- 420 TV lines
- 0.5 Lux



Color Effio-E Dome Security Camera (GW107M)

- Color
- 1/3" Exview HAD CCD II
- Vari-Focal 2.8~12mm Lens
- 36PCS infrared LED
- OSD/2D-DNR/BLC/MD
- 700TV lines
- 0 Lux
- 98 ft IR Distance



GW108M

Color Effio-E Dome Security Camera (GW108M)

- Color
- 1/3" Exview HAD CCD II
- Vari-Focal 2.8~12mm Lens
- 36PCS infrared LED
- OSD/2D-DNR/BLC
- 700 TV lines
- Vandalproof
- 98 ft IR Distance



GW1833P

PIXIM SEAWOLF DPS Camera (GW1833P)

- Color
- 1/3" PIXIM SEAWOLF DPS
- 4-9mm Auto Iris Lens
- 3D Noise Eliminating
- Analog
- 690TVL-E
- Ultra WDR of 120dB



G-63W

32 x Digital Zoom Digital WDR box camera (G-63W)

- Color
- 1/3" interline transfer CCD
- 0.00039 lux(sense up, 256x)
- OSD menu
- 32 x Digital Zoom
- 600 TV lines
- 3DNR function
- RS485 protocol

Outdoor Security Cameras



GW645R

Outdoor IR Security Camera (GW645R)

- Color
- 1/4" SONY CCD
- 3.6mm Lens
- 12PCS infrared LED
- Analog
- 420TV lines
- 0 Lux
- 33 ft IR Distance



GW646

Outdoor IR Security Camera (GW646)

- Color
- 1/4" SONY CCD
- 3.6mm Lens
- 24PCS infrared LED
- Analog
- 420TV Lines
- 0 Lux
- 65.6 ft IR Distance



GW650

Outdoor IR Security Camera (GW650)

- Color
- 1/4" SONY CCD
- 3.6mm Lens
- 26PCS infrared LED
- Analog
- 420TV Lines
- 0 Lux
- 82 ft IR Distance



GW646W

Outdoor IR Security Camera (GW646W)

- Color
- 1/3" SONY CCD
- 3.6mm Lens
- 24PCS infrared LED
- Analog
- 420 TV lines
- 0 Lux
- 65.6 ft IR Distance



GW648W

Outdoor IR Security Camera (GW648W)

- Color
- 1/3" SONY CCD
- 3.6mm Len
- 24PCS infrared LED
- Analog
- 480 TV lines
- 0 Lux
- 65.6 ft IR Distance



GW741

Outdoor IR Security Camera (GW741)

- Color
- 1/3" SONY CCD
- 3.6mm Len
- 30PCS infrared LED
- Analog
- 420 TV lines
- 0 Lux
- 82 ft IR Distance



GW635LG

Outdoor IR Security Camera (GW635LG)

- Color
- 1/3" Color CCD
- 3.6mm Lens
- 23PCS infrared LED
- Analog
- 520 TV Lines
- 0 Lux
- 65.6 feet IR Distance



GW648

Outdoor IR Security Camera (GW648)

- Color
- 1/4" SONY CCD
- 3.6mm Lens
- 24PCS infrared LED
- Analog
- 540 TV Lines
- 0 Lux
- 65.6 feet IR Distance

Outdoor Security Cameras



GW630A

Outdoor IR Security Camera (GW630A)

- Color
- 1/3" SONY CCD
- 3.6mm Lens
- 30PCS infrared LED
- Analog
- 520 TV Lines
- 0 Lux
- 92 feet IR Distance



GW745L

Outdoor IR Security Camera (GW745L)

- Color
- 1/3" SONY CCD
- 3.6mm Lens
- 30PCS infrared LED
- Analog
- 540 TV Lines
- 0 Lux
- 82 feet IR Distance



GW632A

Outdoor IR Security Camera (GW632A)

- Color
- 1/3" SONY CCD
- 6mm CS Mount Lens
- 32PCS infrared LED
- Analog
- 520 TV Lines
- 0 Lux
- 164 feet IR Distance



GW630L

Outdoor IR Security Camera (GW630L)

- Color
- 1/3" SONY CCD
- 3.6mm Lens
- 30PCS infrared LED
- Analog
- 560 TV Lines
- 0.001 Lux
- 92 feet IR Distance



GW745H

Outdoor IR Security Camera (GW745H)

- Color
- 1/3" SONY CCD
- 3.6mm Lens
- 30PCS infrared LED
- Analog
- 560 TV Lines
- 0 Lux
- 82 feet IR Distance



GW704R

Outdoor IR Security Camera (GW704R)

- Color
- 1/3" SONY CCD
- Vari-Focal 4~9mm Lens
- 36PCS infrared LED
- Analog
- 560TV Lines
- 0 Lux
- 132 feet IR Distance



GW632L

Outdoor IR Security Camera (GW632L)

- Color
- 1/3" SONY CCD
- 6mm Lens
- 48PCS infrared LED
- Analog
- 560 TV lines
- 0 Lux
- 132 ft IR Distance



GW2011A

Outdoor IR Security Camera (GW2011A)

- Color
- 1/3" SONY CCD
- Vari-Focal 4~9mm Lens
- 30PCS infrared LED
- Analog
- 520 TV lines
- 0 Lux
- 82 ft IR Distance

Outdoor Security Cameras



GW320A

Outdoor IR Security Camera (GW320A)

- Color
- 1/3" SONY CCD
- 6mm CS lens
- 48 x ϕ 8 + 24 x ϕ 5 pcs IR LEDs
- Analog
- 420 TV lines
- 0 Lux
- 328 ft IR Distance



GW706A

Outdoor IR Security Camera (GW706A)

- Color
- 1/3" Color CCD
- Vari-Focal 4~9mm Lens
- 42PCs IR LED
- Analog
- 540 TV Lines
- 0 Lux
- 114.8 ft IR Distance



GW2011L

Outdoor IR Security Camera (GW2011L)

- Color
- 1/3" SONY CCD
- Vari-Focal 4~9mm Lens
- 82 feet IR Distance
- Analog
- 560 TV lines
- 0 Lux
- 82 ft IR Distance



GW320B

Outdoor IR Security Camera (GW320B)

- Color
- 1/3" SONY CCD
- 6mm CS lens
- 48 x ϕ 8 + 24 x ϕ 5 pcs IR LEDs
- Analog
- 540 TV lines
- 0 Lux
- 328 ft IR distance



GW706H

Outdoor IR Security Camera (GW706H)

- Color
- 1/3" Color CCD
- Vari-Focal 4~9mm Lens
- 42PCs IR LED
- Analog
- 560 TV Lines
- 0 Lux
- 114.8 ft IR Distance



GW639WD

Outdoor WDR IR Security Camera (GW639WD)

- Color
- 1/3" SONY CCD
- 4mm Lens
- 36PCs IR LED
- Wide Dynamic Range
- 600 TV Lines
- 0 Lux
- 98.4 ft IR Distance



GW612WD

Outdoor WDR IR Security Camera (GW612WD)

- Color
- 1/3" SONY CCD
- 3.6mm lens
- 48PCS infrared LED
- Wide Dynamic Range
- 600TV Lines
- 0 Lux
- 131 ft IR Distance



GW733H

Outdoor WDR IR Security Camera (GW733H)

- Color
- 1/3" SONY CCD
- 3.6mm Lens
- 30PCS infrared LED
- Wide Dynamic Range
- 600 TV lines
- 0 Lux
- 82 ft IR Distance

Outdoor Security Cameras



GW780A

Outdoor IR Security Camera (GW780A)

- Color
- 1/3" SONY CCD
- Vari-Focal 8~20mm Lens
- 72PCS IR LED
- Analog
- 520 TV lines
- 0 Lux
- 196.85 ft IR Distance



GW613WD

Outdoor Effio-E IR Security Camera (GW613WD)

- Color
- 1/3" Exview HAD CCD II
- 3.6mm lens
- 48PCS infrared LED
- OSD/2D-DNR/BLC
- 700 TV lines
- 0 Lux
- 164 ft IR Distance



GW706WD

Outdoor Effio-E IR Security Camera (GW706WD)

- Color
- 1/3" Exview HAD CCD II
- 2.8~10mm varifocal lens
- 42PCS infrared LED
- OSD/2D-DNR/BLC
- 700 TV lines
- 0 Lux
- 131 ft IR Distance



GW2011WD

Outdoor WDR IR Security Camera (GW2011WD)

- Color
- 1/3" SONY CCD
- Vari-Focal 4~9mm lens
- 30PCS infrared LED
- Wide Dynamic Range
- 700TV Lines
- 0 Lux
- 82 feet IR Distance



GW30WD

Outdoor Effio-E IR Security Camera (GW30WD)

- Color
- 1/3" Exview HAD CCD II
- 2.8~12mm varifocal lens
- 42PCS infrared LED
- OSD/2D-DNR/BLC
- 700 TV lines
- 0 Lux
- 115 ft IR Distance



GW707H

Long Distance Day Night Camera (GW707H)

- Color
- 1/3" SONY CCD
- 4~9mm varifocal lens
- 42PCS infrared LED
- Wide Dynamic Range
- 600TV Lines
- 0 Lux
- 131 feet IR Distance



GW50WD

Outdoor Effio-E IR Security Camera (GW50WD)

- Color
- 1/3" Exview HAD CCD II
- 2.8~12mm varifocal lens
- 72PCS infrared LED
- OSD/2D-DNR/BLC
- 700 TV lines
- 0 Lux
- 164 ft IR Distance



GW781A

Outdoor Effio-E IR Security Camera (GW781A)

- Color
- 1/3" Exview HAD CCD II
- 9~22mm varifocal lens
- 72PCS infrared LED
- OSD/2D-DNR/BLC
- 700 TV lines
- 0 Lux
- 164 ft IR Distance

Outdoor Security Cameras



GS70W

Long Distance Day Night Camera (GS70W)

- Color
- 1/3" SONY DS CCD SAMSUNG SV-IV DSP
- 9~22mm auto iris lens
- 30PCS infrared LED
- 560 TV Lines
- 0 Lux
- 131 feet IR Distance

PIXIM 690TVL-E



GW1518

Outdoor PIXIM SEAWOLF DPS Camera (GW1518)

- Color
- 1/3" PIXIM SEAWOLF DPS
- Ultra Wide Dynamic Range, 120dB
- 70PCS infrared LED
- Analog
- 690TVL-E
- 3D Noise Eliminating
- 328 feet IR Distance

Hidden Security Cameras



GW8310A

Plug-shaped hidden camera. 3.7mm Taper Pinhole Lens. 1/3" SONY CCD, 0.8 Lux, 420 TVL. Audio Input and Light Weight. Elegant Design for Use In Office, Warehouse or Domestic Applications. NTSC:510X492



GW280

1/4" Sony CCD Mini Full Cone Pinhole Camera. You Can Virtually Hide it Anywhere. Dimension: 25x25mm/30x30mm. Super Low 0.05Lux Works Great In Low Light



GW831

1/3" OmnVision CMOS Mini Pinhole Camera. You Can Virtually Hide it Anywhere. Super Low 0Lux Works Great In Low Light



GW832

1/3" OmnVision CMOS Mini Pinhole Camera. You Can Virtually Hide it Anywhere. Super Low 0Lux Works Great In Low Light



GW8230SB

PIR Spy Color Camera. 1/3" Sony CCD, 480 TV Lines, 3.7mm Wide Angle View. Super Small Pinhole Hidden Camera Shaped Like a PIR Motion Detector.



GW-MC4

1/3" SONY CCD Small Hidden Camera, 420TV line. You Can Virtually Hide it Anywhere. Dimension: 36 x 40 x 41. Super Low 0.1Lux Works Great In Low Light



GW810CP

1/3" SONY CCD Small Pinhole Camera, 425TV line. You Can Virtually Hide it Anywhere. Dimension: 35.5mm/35.5mm. Super Low 0.5Lux Works Great In Low Light



GW-D2310

1/3" SONY CCD Small Hidden Camera, 420TV line, 3.7mm lens. You Can Virtually Hide it Anywhere. Great In Low Light



GW-D2311

1/3" SONY CCD Small Hidden Camera, 420TV line, 2.97mm lens. You Can Virtually Hide it Anywhere. Great In Low Light

Hidden Security Cameras



GW-BB7

1/3" SONY CCD Small Hidden Camera, 540TV line. You Can Virtually Hide it Anywhere. Dimension: 38 x 105mm. Super Low 0.5Lux Works Great In Low Light



GW660CP

1/3" Sony CCD Small Pinhole Camera, 525 TV Line. You Can Virtually Hide it Anywhere. Dimension: 35.5mm/35.5mm. Super Low 0.8Lux Works Great In Low Light



GW-D1910

1/3" SONY CCD Small Hidden Camera, 550TV line, 2.97mm lens. You Can Virtually Hide it Anywhere. Great In Low Light



GW8330

Functional Smoke Detector Color Covert Camera, SONY Color CCD Image Sensor, 540 TVLines, 3.7mm Pinhole Lens, Mini Illumination 0.1 LUX. Alarm Output Function



GW-D2155

1/3" SONY CCD 3D-DNR Hidden Camera, 550TV line, Bullet Camera with DNR function. 2.97mm lens. You Can Virtually Hide it Anywhere. Great In Low Light



GWC405

1/3" SONY Super HAD Color CCD Square Camirror, 540TV Line, Built-in 4.3mm lens. Hidden camera behind it. Great Image, Great for Entrance. Help the cashier to receive an exact observation



GW150H

Halogen IP55 Auto Detector Light Camera / Hidden / Covert / Pin-hole Camera (Floodlight). 1/3" SONY Super HAD Color CCD, 540 TV Lines. Halogen Tube: 150W.



GWC406

1/3" SONY Super HAD Color CCD Oval Camirror, 540TV Line, Built-in 4.3mm lens. Hidden camera behind it. Great Image, Great for Entrance. Help the cashier to receive an exact observation



GW500H

Halogen IP55 Auto Detector Light Camera / Hidden / Covert / Pin-hole Camera (Floodlight). 1/3" SONY Super HAD Color CCD, 540 TV Lines. Halogen Tube: 500W.

Long Distance Security Cameras



GW359L

License Plate Box Camera. 1/3" SONY CCD, color 560TVL, B/W 700TVL, 0.002 Lux, 5-50mm auto iris lens, NTSC

Hybrid LED



GW8051

Anti-Crime Smart Dual Light LED Camera, Hybrid LED 530TVL, 3.7mm~12mm Varifocal lens. Auto Iris + IR Cut. Supported motion and PIR detection system with white light and IR LED.



GW560R-G

License Plate Camera. 1/3" SONY CCD, color 600TVL, B/W 700TVL, 0 Lux, 9~22mm varifocal lens, 42pcs IR LED, 98.4 ft IR Distance.

WDR



G-63W

1/3" SONY CCD Digital WDR Box Camera & External IR. 600 TV lines. WDR (Wide Dynamic Range). OSD Menu. Low Illumination 0.1 Lux. 98.42 ft IR Distance. Great Image, Great for Entrance.



GS70W

Long Distance Day Night Camera with Bracket. 1/3" SONY DS CCD SAMSUNG SV-IV DSP, color 560TVL, B/W 700TVL, IR 131.23 feet, 9-22mm auto iris lens



GW7121

Professional Long Distance Viewing Smart Shirt IR Camera. 1/3" SONY Super HAD CCD Camera. 540 TV lines, 6 ~ 50 mm / F1.6 varifocal lens, 42pcs IR LED (36pcs Piranha / 6pcs Reflection), 262 ft IR Distance. Removable IR Cut Filter Built-in, accurate focus for Day & Night. OSD Menu. Great Image.

PIXIM 690TVL-E



GW1518

Professional IR Waterproof Camera, with 1/3" PIXIM SEAWOLF DPS, 690TVL-E, WDR of 120dB, 3D Noise Eliminating Technology



GWNA32

Mini Low Speed outdoor Pan/Tilt dome Camera. 30 Degree/second with 580 TV line camera NTSC with 4~9mm lens.



GWNA51

Mini High Speed indoor PTZ dome Camera. 240 Degree/second with high resolution camera, 10*Zoom, day/night, NTSC. Pendant bracket, power supply. Chromium coating. SONY CCD, F=3.8 to 38mm(F1.8 to 3.2) 10* optical zoom, 10* digital zoom. 580 TVL, Color: 0.7 Lux/F1.8 (50 IRE) B/W: 0.02Lux/F1.8 (50 IRE)



GWNA52

Mini High Speed outdoor PTZ dome Camera. 240 Degree/second with high resolution camera, 10*Zoom, day/night, anti-vandal with wall mount bracket power supply. SONY CCD, F=3.8 to 38mm(F1.8 to 3.2) 10* optical zoom, 10* digital zoom. 580 TVL, Color: 0.7 Lux/F1.8 (50 IRE) b/W: 0.02Lux/F1.8 (50 IRE)



GWNA7D2

Middle Speed outdoor PTZ dome Camera. 100 Degree/Second with wall mount bracket power supply with 27*zoom day/night. SONY CCD, F=1.5-F3.6, F=3.25mm~88mm. 27* optical zoom, 12*digital zoom. Color Mode: 0.003 (0.6) Lux B/W Mode: 0.0001 (0.1) Lux, 600 TV Lines



GW53W

Indoor/Outdoor high speed dome 1/4" Sony CCD 230X zoom lens camera, Low Lux, super longer range zoom, Special fully control Housing Design with motor built-in, High speed controlling camera with adjustable Lens



GWPT-722RI

Intelligent IR Middle Speed Outdoor PTZ dome Camera. 22 times outdoor 360 degree continuous turning, 64 preset point, 520 TVL. It fits for a wide range of applications such as intelligent building, bank, street of city, airport, station etc ...



GWNA8D2

Intelligent IR Middle Speed Outdoor PTZ dome Camera, 18x optical and 12x digital day/night NTSC. Horizontal Rotation Speed 1~160°/s. IR distance is 140M. It fits for a wide range of applications such as intelligent building, bank, street of city, airport, station etc ...



GWPT-723RI-H

Intelligent IR Middle Speed Outdoor PTZ dome Camera. 23 times outdoor 360 degree continuous turning, 64 preset point, 560 TVL. It fits for a wide range of applications such as intelligent building, bank, street of city, airport, station etc ...

PTZ Security Cameras



GWPT-727RIII-H

Intelligent IR High Speed Outdoor PTZ dome Camera. 27 times optical zoom , 10 times digital zoom outdoor 360 degree continuous turning, 128 preset point, 580 TVL. It fits for a wide range of applications such as intelligent building, bank, street of city, airport, station etc ...



GWPT-722RI-AL-IP

Intelligent IR Middle Speed Outdoor IP PTZ dome Camera. 22X Optical Zoom, 100M IR Range, Pan angle: 360° Tilt: 180°, 64 preset point, 480 TVL. It fits for a wide range of applications such as intelligent building, bank, street of city, airport, station etc ..



GWPT-722RIII-IP

Intelligent IR High Speed Outdoor PTZ dome Camera. 22 times optical zoom, outdoor Horizontal 360° continuous turning, 128 preset point, 580 TVL. It fits for a wide range of applications such as intelligent building, bank, street of city, airport, station etc ...



GWPT-736RIII

Intelligent IR High Speed Outdoor PTZ dome Camera. 36 times optical zoom, 12 times digital zoom outdoor 360 degree continuous turning, 128 preset point, 480 TVL. It fits for a wide range of applications such as intelligent building, bank, street of city, airport, station etc ...

PTZ Controller



GW303

Security speed dome camera keyboard controller. Up to 32 speed dome cameras. 2000 feet maximum distance communication. Control the pan tilt auto line scan, speed and direction. Set or call the set points and cruise tracks of the dome camera



GW525

Security speed dome camera 2D keyboard controller. Using the joystick to control the speed dome camera. Up to 32 speed dome cameras. 2000 feet maximum distance communication. Control the pan tilt auto line scan, speed and direction. Set or call the set points and cruise tracks of the dome camera



GW505

Security speed dome camera 3D keyboard controller. Using 3 axis joystick to control the Pan/Tilt direction and speed of the dome camera. Up to 32 speed dome cameras. 2000 feet maximum distance communication. Maximum of 255 addressable preset points and 1~6 tours

Ultra Low Illumination Cameras

low illumination



0.001 lux

GW801L

The latest SONY Super HAD II CCD, advanced ISP with 14 bit converter. High resolution 600 TVL ultra low illumination 0.001lux. The built-in 3D DNR engine can effectively control the noise

low illumination



0.001 lux

GW802L

The latest SONY Super HAD II CCD, advanced ISP with 14 bit converter. High resolution 600 TVL, ultra low illumination 0.001lux. The built-in 3D DNR engine can effectively control the noise.

Hybrid LED Cameras

Hybrid LED



GW8302

Anti-Crime Smart Dual Light LED Camera, Hybrid LED 420TVL, 6mm lens. Supported motion and PIR detection system with white light and IR LED.

Hybrid LED



GW8051

Anti-Crime Smart Dual Light LED Camera, Hybrid LED 530TVL, 3.7mm~12mm Varifocal lens. Auto Iris + IR Cut. Supported motion and PIR detection system with white light and IR LED.

IP Security Cameras



P2P Network Camera (GW136)

- Color
- 1/4" Color CMOS Sensor
- 640 x 480 Pixels
- Multi-level users management
- Pan/Tilt control
- Auto IR-LED illumination
- 0.5Lux
- Motion detection alert



IP Camera (GW1350)

- Color
- 1/4" Color CMOS Sensor
- 640 x 480 Pixels
- Multi-level users management
- Simple to setup, Friendly GUI
- Auto IR-LED illumination
- 0.5Lux
- Motion detection alert



IP Camera (GW145)

- Color
- 1/4" Color CMOS Sensor
- 640 x 480 Pixels
- Integrated wireless alarm gateway function
- User can view image through IE
- two-way audio function
- Support alarm linkage



IP Camera (GW1338CD)

- Color
- Pan:0°~355°, Tilt:0°~90°
- 98.42 feet IR distance
- Multi-Level User Access With Password Protection
- 520TVL
- 3G(WCDMA), SD Card, UPNP
- H.264, MJPEG Video Compression



1/3" 2.0-megapixel IP Camera (GW1560)

- Color
- 1/3" 2.0-megapixel
- 1280x720 Pixels
- Built-in Web server
- 1 Lux illumination
- SoC ARM9 processor
- Up to 30 frames per second
- RS485/RS232 serial port



1/3" 2.0-megapixel IP Camera (GW1340CM)

- Color
- 1/3" 2.0-megapixel
- 1600x1200 Pixels
- H.264/MJPEG compression
- SD2.0, SDHC storage card
- High S/N ratio, clear picture
- Support image masking
- motion detection, network checking



1 / 3" 2.0-megapixel IP Camera (GW2200)

- Color
- 1 / 3" 2.0-megapixel
- H.264 Main Profile@Level 3
- Up to 10 viewers can directly access
- 0.1 Lux illumination
- SoC ARM9 processor
- Up to 30 frames per second
- Auto-recovery



1 / 3" 2.0-megapixel IP Camera (GW2230)

- Color
- 1/3" Sony progressive scanning 1.3 megapixels CCD sensor
- H.264 Main Profile@Level 3
- Up to 10 viewers can directly access
- 12mm fixed focus lens
- Up to 30 frames per second
- Auto-recovery

Wireless Cameras



GW830

Wireless 2.4GHz wireless camera security surveillance system. Wireless receiver and wireless color CMOS camera. Suitable for monitoring children, old people and house, companies, shops and factories



GWS305

Mini Wireless 2.4GHz wireless camera security surveillance system. Wireless receiver and wireless color CMOS camera. Suitable for monitoring children, old people and house, companies, shops and factories



GW4001

A great wireless camera system for DVR & TV. 1 x 1/3" CMOS Wireless Cameras, 380TV line and 1 x 2.4GHz Wireless Receiver. Suitable for monitoring children, old people and house, companies, shops and factories



GWS200

Mini Wireless 2.4GHz wireless camera security surveillance system. Wireless USB DVR and wireless color CMOS camera. Suitable for monitoring children, old people and house, companies, shops and factories



GW4002

great wireless camera system for DVR, TV, and PC. 1 x 1/3" CMOS Wireless Cameras, 380TV line and 1 x 2.4GHz Wireless Receiver. Suitable for monitoring children, old people and house, companies, shops and factories



GW817DF1

2.4GHz Digital (with stable&encrypted video)Wireless Security Kits. Up to 200 meters transmission in open area. Suitable for monitoring children, old people and house, companies, shops and factories



GW820

Wireless 2.4GHz wireless camera security surveillance system. Wireless receiver and wireless color CMOS camera. Suitable for monitoring children, old people and house, companies, shops and factories



GW821

Wireless 2.4GHz wireless camera security surveillance system. Wireless receiver and wireless color CMOS camera. Suitable for monitoring children, old people and house, companies, shops and factories



GW822

Wireless 2.4GHz wireless camera security surveillance system. Wireless receiver and wireless color CMOS camera. Suitable for monitoring children, old people and house, companies, shops and factories

Wireless Cameras



GW825

Wireless 2.4GHz wireless camera security surveillance system. Wireless receiver and wireless color CMOS Bear camera. Suitable for monitoring children, old people and house, companies, shops and factories



GW826

Wireless 2.4GHz wireless camera security surveillance system. Wireless receiver and wireless color CMOS camera. Suitable for monitoring children, old people and house, companies, shops and factories



GW4003

A great wireless camera system for DVR, TV, and PC. 4 x 1/3" CMOS Wireless Cameras, 380TV line and 1 x 2.4GHz Wireless Receiver. Suitable for monitoring children, old people and house, companies, shops and factories



GW8005WSC

2.4G Wireless 4 Channel security surveillance system. A great wireless camera system. 380TV line 1/3" color CCD Wireless Camera and 2.4GHz Wireless Receiver. Suitable for monitoring children, old people and house, companies, shops and factories



GWUSBC

Professional 4CH 2.4GHz Digital Wireless Security Kit . Suitable for monitoring children, old people, house, companies and shops



GW708U

2.4G Wireless 4 Channel security surveillance system. A great wireless camera system. 380TV line 1/3" color CCD Wireless Camera and 2.4GHz Wireless Receiver. Suitable for monitoring children, old people and house, companies, shops and factories



GW9104V

4 Channel Security DVR (GW9104V)

- Select a hard drive
- iPhone Viewing
- Video Output: 4-CH BNC Input/2-CH BNC Output/1-VGA Output
- Manual/schedule/Motion Detection Recording Modes
- 30fps Frame Rate
- IE browsing or Netviewer software browsing
- 4 Channel H.264 DVR
- H.264 Video Compression
- USB backup

GW9104V (VGA)
GW9104 (No VGA)



GW2544SV

4 Channel Security DVR (GW2544SV)

- Select a hard drive
- iPhone Viewing
- Video Output: BNC 4 Input / VGA 1 Output BNC 1 Output
- Manual/schedule/Motion Detection Recording Modes
- 30fps Frame Rate
- MP4 or H.264 Raw backup
- IE Browser Live Monitor
- 4 Channel H.264 DVR
- H.264 Video Compression

GW2544SV (VGA)
GW2544S (No VGA)



GW9003

4 Channel Security DVR (GW9003)

- Select a hard drive
- Well Image quality, High definition
- 30fps Frame Rate
- Video Input / Output: 4-CH Video Input, 1-CH Video Output
- Support Mutli recording mode: Continuous, Motion Detection
- Supports IR Remote Remote Controller
- IE Browser Live Monitor
- 4 Channel DVR
- MPEG4 Compression
- USB 2.0 backup



GW2201

4 Channel Security Vehicle DVR (GW2201)

- Select a hard drive
- AVI File Format
- 30fps Frame Rate
- Video Output: 1 channel, 1.0V, p-p, 75Ω, BNC
- Date and time stamp records onto footage
- Compact size & lightweight, much easier for installation
- 4 Channel Vehicle DVR
- H.264 High Profile Video Compression
- 1248 × 832 Record Resolution



GW9108V

8 Channel Security DVR (GW9108V)

- Select a hard drive
- iPhone Viewing
- Video Output: 8-CH BNC Input/2-CH BNC Output/1-VGA Output
- Manual/schedule/Motion Detection Recording Modes
- 30fps Frame Rate
- IE browsing or Netviewer software browsing
- 8 Channel H.264 DVR
- H.264 Video Compression
- PTZ Control

GW9108V (VGA)
GW9108 (No VGA)



GW2548SV

8 Channel Security DVR (GW2548SV)

- Select a hard drive
- iPhone Viewing
- 30fps Frame Rate
- Video Output: BNC 8 Input / VGA 1 Output BNC 1 Output
- Time & date search easy access
- IE Browser Live Monitor
- 8 Channel H.264 DVR
- H.264 Video Compression
- MP4 or H.264 Raw backup

GW2548SV
GW2558SV



GW2558SV
(VGA & DVD)



GW3008

8 Channel Security Full D1 H.264 DVR (GW3008)

- Select a hard drive
- iPhone, Andriod, & Blackberry
- 240FPS@D1 RecordFrame Rate
- Video: BNC 8 Input / CVBS Output/Spot Out/Video Loop/VGA Output/HDMI
- IP or DDNS, LAN or IE browsing
- Backup files in DAV format
- Full D1, HDMI & VGA support
- H.264 Baseline Compression
- USB 2.0 backup

**GW3008 (8CH)
GW3016 (16CH)**



GW2898

8 Channel Color LCD Security DVR (GW2898)

- Select a hard drive
- iPhone Viewing
- 30fps Frame Rate (CIF)
- PTZ Control
- Video Input: BNC 8 Input / 1 Output
- Audio Input: RCA 8 Input
- Simultaneous Playback/Record/Network
- IE Browser Live Monitor
- H.264 Video Compression
- USB 2.0 backup

**GW2854 (15"/ 4CH)
GW2868 (15"/ 8 CH)
GW2898 (19"/ 8 CH)**



GW9016V

16 Channel Security DVR (GW9016V)

- Select a hard drive
- iPhone Viewing
- Always/schedule/manual/motion detection/sensor triggered/Net-viewer recording
- 704x480 Display Resolution
- PTZ Control
- IE browsing or Netviewer software browsing
- 16 Channel H.264 DVR
- Video: H.264/ Audio 8KHz*16bit ADPCM



GW2556SV

16 Channel Security DVR (GW2556SV)

- Select a hard drive
- iPhone Viewing
- Video Output: 16 BNC Input / 1 VGA Output 1 Main Output 1 Call Output
- Audio Input: 16 RCA Input / 1 Output
- PTZ Control
- IE Browser Live Monitor
- 16 Channel H.264 DVR
- H.264 Baseline Compression
- Sensor In/Out: 16CH Input / 4CH Output
- 480 FPS @ CIF Record Frame Rate
- MP4, AVI or H.264 Raw Backup



GW2556HD

16 Channel Security HDMI DVR (GW2556HD)

- Select a hard drive
- iPhone, Andriod, & Blackberry
- 100 FPS@D1 RecordFrame Rate
- Video Output: BNC 16 Input / 1 Output /1 CH Spot
- IP or DDNS, LAN or IE browsing
- Playback: Normal, Fast Forward, Slow Forward, Rewind, Single Step
- HDMI & VGA support
- H.264 Baseline Compression
- USB 2.0 backup



4 Ch DVR Capture Card (GW804S)

- 4CIF preview resolution
- Adaptor high quality Techwell TW2815 chipset
- CIF compression Resolution: 352x240 (NTSC), 352x288 (PAL)
- Support Intel,AMD,SIS,VIA,NVidia chip Mainboard,support Intel,AMD CPU
- Support WINDOWS 2000/XP/VISTA



4 Ch DVR Capture Card (GW9404)

- 4 Channel DVR Card for PC
- 640 X 480 Screen Resolution
- Continuous & Motion Detection Recording
- TCP/IP Remote Internet Camera Viewing
- Supports windows 2000/ XP



4 Ch DVR Capture Card (GW104Q9)

- Run under Windows XP 32bit OS, Windows Vista 32bit OS, Windows 7 32bit OS
- 6805 chipset 10-bit ADCs image quality
- Lightning-Proof design
- Adjust the setting for any channel, and can be applied to other channels
- Snapshot the dynamic picture or static picture while playback




8 Ch DVR Capture Card (GW108Q9)

- Run under Windows XP 32bit OS, Windows Vista 32bit OS, Windows 7 32bit OS
- 6805 chipset 10-bit ADCs image quality
- Adjust the setting for any channel, and can be applied to other channels
- Snapshot the dynamic picture or static picture while playback



8 Ch DVR Capture Card (GW9808)

- 8 Channel DVR Card for PC
- 640 X 480 Screen Resolution
- Continuous & Motion Detection Recording
- TCP/IP Remote Internet Camera Viewing
- Supports windows 2000/ XP



8 Ch DVR Capture Card (GW808S)

- High quality Techwell TW2815 chipset
- CIF compression Resolution: 352x240 (NTSC), 352x288 (PAL)
- Support Intel,AMD,SIS,VIA,NVidia chip Mainboard,support Intel,AMD CPU
- Support WINDOWS 2000/XP/VISTA



16 Ch DVR Capture Card (GW216Q9)

- Run under Windows XP 32bit OS, Windows Vista 32bit OS, Windows 7 32bit OS
- 6805 chipset 10-bit ADCs image quality
- Adjust the setting for any channel, and can be applied to other channels
- Snapshot the dynamic picture or static picture while playback



16 Ch DVR Capture Card (GW816S)

- High quality Techwell TW2815 chipset
- CIF compression Resolution: 352x240 (NTSC), 352x288 (PAL)
- Support Intel,AMD,SIS,VIA,NVidia chip Mainboard,support Intel,AMD CPU
- Support WINDOWS 2000/XP

Siamese Cable



CCTV Cable - Siamese Power and Video 25 Feet (GW25CAW)
- 25 feet pre-made cable BNC and Power Ready To Go
- white



CCTV Cable - Siamese Power and Video 60 Feet (GW60CAW)
- 60 feet pre-made cable BNC and Power Ready To Go
- white



CCTV Cable - Siamese Power and Video 100 Feet (GW100CAW)
- 100 feet pre-made cable BNC and Power Ready To Go
- white



CCTV Cable - Siamese Power and Video 125 Feet (GW125CAW)
- 125 feet pre-made cable BNC and Power Ready To Go
- white



CCTV Cable - Siamese Power and Video 200 Feet (GW200CAW)
- 200 feet pre-made cable BNC and Power Ready To Go
- white



CCTV Cable - Power, Audio and Video 50 Feet (GW-VAP50)
- Siamese
- 50 feet pre-made cable BNC + Audio + Video and Power Ready To Go
- Black



CCTV Cable - Power, Audio and Video 100 Feet (GW-VAP100)
- Siamese
- 100 feet pre-made cable BNC + Audio + Video and Power Ready To Go
- Black



CCTV Cable - Siamese Power and Video 500 Feet (GW500RG59)
- 500 feet pre-made cable BNC and Power Ready To Go
- white



CCTV Cable - Siamese Power and Video 1000 Feet (GW1000RG59)
- 1000 feet pre-made cable BNC and Power Ready To Go
- white

Cat-5E



Cat-5E Cable 10 Feet (GWCAT10R)

- Category 5E UTP RJ45 Patch Cable Red - 10 ft
- Enhanced Cat5 cables transfer data, voice and video up to 350Mhz



Cat-5E Cable 10 Feet (GWCAT25B)

- Category 5E UTP RJ45 Patch Cable Blue - 25 ft
- Enhanced Cat5 cables transfer data, voice and video up to 350Mhz



Cat-5E Cable 10 Feet (GWCAT50Y)

- Category 5E UTP RJ45 Patch Cable Yellow - 50 ft
- Enhanced Cat5 cables transfer data, voice and video up to 350Mhz



Cat-5E Cable 10 Feet (GWCAT100G)

- Category 5E UTP RJ45 Patch Cable Green - 100 ft
- Enhanced Cat5 cables transfer data, voice and video up to 350Mhz



Category 5 Cable 1000 Feet (GWCAT5E)

- Category 5E Cable - 1000 ft Box
- 4 x 2 x 24 AWG
- Unshield Twisted Pair
- Rip Cord
- Flexible PVC Jacket
- High Performance Data Cable
- Installer-friendly Cable Shipped in Reel-in-box Packaging
- Voice and Data communications.

VGA Cable



CCTV Cable - VGA "Y" Splitter (GWVGA1116)
- VGA "Y" Splitter - (1) HD15M to (2) HD15 F - 6"



VGA Monitor Replacement Cable HD15 M/M - 6ft (GWVGA112)
- Replacement VGA Cable; HD15 Male to Male; Beige



VGA Monitor Extension Cable HD15 M/F - 15ft (GWVGA110E)
- Molded with thumbscrews; wired straight through



VGA Monitor Cable HD15 Male to Female - 25ft (GWVGA110G)
- Replacement VGA Cable; HD15 Male to Female; Beige



25FT VGA Cable M/M 15 pin HD D-Sub (HD-15) (GWVGA113)
- Male to Male 15 pin HD D-Sub (HD-15)



SVGA / VGA Monitor Replacement Cable (GWVGA112MDS)
- SVGA / VGA Monitor Replacement Cable HD15 M/M -50ft Double

HDMI Cable



6' HDMI Male to Male Multimedia Cable/Gold (GWHDMI6W)
- 6' HDMI Male to Male Multimedia Cable/Gold. This premium HDMI cable supports high-bandwidth, uncompressed video and multi-channel digital audio, maximum video performance, prevents signal loss & screen ghosting.



10' HDMI Male to Male Multimedia Cable (GWHDMI10B)
- 10' HDMI Male to Male Multimedia Cable. This premium HDMI cable supports high-bandwidth, uncompressed video and multi-channel digital audio, maximum video performance, prevents signal loss & screen ghosting.

Surveillance Tools



- Coaxial Cable Stripper (GW-T5019)**
- Cable stripping tool
 - For RG-58(3C2V),RG-59/62,RG6



- Ratchet Control Crimping Tool (GW-T5021)**
- For cutting wire, 30mm max. stripping wire 6.0~2.6mm² and crimping terminals
 - Automatic rebound spring
 - No damaging of the conductor core



- Impact Punch Down tool (GW-T5024)**
- For seating wire into terminal block or cut off wire end after terminated
 - Hardened reversible blade



- Impact Punch Down tool (GW-T5023)**
- Hand tools
 - Impact Punch Down Tool
 - For seating wire into terminal block or cut off wire end after terminated



- Modular Crimping tool (GW-T5068)**
- For cuts-strips-crimps 2 type of plug in 1
 - Crimping tool



- Universal stripping tool (GW-T5005)**
- Stripping tool for UTP and STP cable
 - Strips RG59/6/11/7 coaxial cable
 - Stripping flat telephone cable
 - Used cutter



- Crimping tool (GW-T5006)**
- Hand tool
 - Ratchet crimping tool
 - Multi-function telephone tool crimp,cuts and strips to make telephone terminals quick



- Self-Adjusting Cutter-Stripper (GW203MS)**
- Strips wire (12- to 22-gauge) with one pull of the trigger
 - Use the built-in ruler to measure the amount of insulation you want to strip
 - Splice into a wire without cutting it
 - Adjusts automatically to solid or stranded wire
 - A second blade cuts your wire cleanly



- Cable Tie Fastening Tool (GW-T5089)**
- Plastic cable tie gun
 - For tensioning and cut-off cable tie

Surveillance Tools



9" Hex Series Crimping Tool (GW-T5009)

- Hand cable stripper
- For crimping F,N,BNC,TNC,UHF,ST,SC,SMA etc.connectors.
- Cable crimping tool



Compression Tool (GW-T5010)

- Coaxial cable crimping tools
- Connects radial connectors to coaxial cable
- Customize the length of cable used



Compression Tool (GW-T5008)

- Coaxial cable cutting tool
- Compression tools
- Works on Augat/T&B Snap-N-Seal
- Connectors,Paladin SealTite



Crimping Tool (GW-T5082)

- Hand crimping tool
- Crimping for BNC and twist pair
- For Waterproof Connectors "F",BNC,RCA/RG-58(3C),RG-59(4C),RG-6(5C)



Adjustable Crimp Tool (GW-T5081)

- Compression tool
- Crimping tool
- Adjustment for Crimping different length connectors
- For use on RG-59(4C)and RG-6(5C)



Professional Compression Tool (GW-T5480)

- Wire crimping tools
- Professional connectors crimping tools
- For use on RG59,RG6,RG11
- F compression connector



DC 1 to 4 Power Splitter Adapter Cable (GW124CA)
- DC 1 to 4 Power Splitter Adapter Cable for CCTV Camera



DC 1 to 8 Power Splitter Adapter Cable (GW128CA)
- DC 1 to 8 Power Splitter Adapter Cable for CCTV Camera



Male Power Pigtail (GW082)
- Male Power Pigtail for connecting camera, Power Cable, Transformer, Easy To Use, Saves Time, No Need To Cut Wire. Crimp And Done.
- 1 Pack contains: 10 pcs



Female Power Pigtail (GW132)
- Female Power Pigtail for connecting camera, Power Cable, Transformer, Easy To Use, Saves Time, No Need To Cut Wire. All You Need Is a Screwdriver.
- 1 Pack contains: 10 pcs



DC 12V 0.5A Power Supply (GW12V0.5A)
- DC 12V 0.5A Power Supply for Security Cameras
- Output: 12V DC 0.5A



DC 12V 800mA Power Supply (GW12V0.8A)
- DC 12V 800mA Power Supply for Security Cameras
- Output: 12V DC 800mA



DC 12V 1A Power Supply (GW12V1A)
- DC 12V 1A Power Supply for Security Cameras
- Output: 12V DC 1A



DC 12V 2A Power Supply (GW12V2A)
- DC 12V 2A Power Supply for Security Cameras
- Output: 12V DC 2A



DC 12V 3A Power Supply (GW12V3A)
- DC 12V 3A Power Supply for Security Cameras
- Output: 12V DC 3A

Power Supply



- DC 12V 5A Power Supply (GW12V5A)**
- DC 12V 5A Power Supply for Security Cameras
- Output: 12V DC 5A



- DC 12V 7A Power Supply (GW12V7A)**
- DC 12V 7A Power Supply for Security Cameras
- Output: 12V DC 7A



- AC24V1A Power Supply (GW24V1A)**
- AC24V1A Power Supply for Security Cameras
- Output: AC24V1A



- AC24V2A Power Supply (GW24V2A)**
- AC24V2A Power Supply for Security Cameras
- Output: AC24V2A



- AC24V3A Power Supply (GW24V3A)**
- AC24V3A Power Supply for Security Cameras
- Output: AC24V3A



- AC24V5A Power Supply (GW24V5A)**
- AC24V5A Power Supply for Security Cameras
- Output: AC24V5A



- PTC Camera Power Box for Security Cameras (GW1204-3A)**
- 12V, 4 port, 3A
- Positive Temperature Coefficient (PTC), Auto Reset Fuse
- Wall Mount Metal Box



- PTC Camera Power Box for Security Cameras (GWP1209-10A)**
- 12V, 9 port, 10A
- Positive Temperature Coefficient (PTC), Auto Reset Fuse
- Wall Mount Metal Box



- PTC Camera Power Box for Security Cameras (GWP1218-10A)**
- 12V, 18 port, 10A
- Positive Temperature Coefficient (PTC), Auto Reset Fuse
- Wall Mount Metal Box

Power Supply



- PTC Camera Power Box for Security Cameras (GW2409-5A)**
- 24V, 9 port, 5A
 - Positive Temperature Coefficient (PTC), Auto Reset Fuse
 - Wall Mount Metal Box



- PTC Camera Power Box for Security Cameras (GW2404-10A)**
- 24V, 4 port, 10A
 - Positive Temperature Coefficient (PTC), Auto Reset Fuse
 - Wall Mount Metal Box



- PTC Camera Power Box for Security Cameras (GW2418-10A)**
- 24V, 18 port, 10A
 - Positive Temperature Coefficient (PTC), Auto Reset Fuse
 - Wall Mount Metal Box



- Backup Power Supply for Security Cameras (GW1209-5A-B)**
- 12V, 9 port, 5A
 - Positive Temperature Coefficient (PTC), Auto Reset Fuse
 - Support 1 PCs 12V7AH Battery



- Backup Power Supply for Security Cameras (GW1209-10A-B)**
- 12V, 9 port, 10A
 - Positive Temperature Coefficient (PTC), Auto Reset Fuse
 - Support 1 PCs 12V7AH Battery



- Backup Power Supply for Security Cameras (GW1218-10A-B)**
- 12V, 18 port, 10A
 - Positive Temperature Coefficient (PTC), Auto Reset Fuse
 - Support 1 PCs 12V7AH Battery



- 12V3.5A Power transformer for Security Camera Power Box (GWS12V3.5A)**
- 12V3.5A



- Internet Surge Protector (GW2250)**
- Internet Surge Protector. Clear Power. Auto Shut-Off Safeguard

Infrared Red Illuminator



60 pcs IR LED Infrared Red Illuminator (GWIR50)
- 60 pcs of strong powered IR LED. Merit Li-Lin PRH-5218. IP 67 High efficiency infrared LED, radiant distance - 40meter



12 pcs Strong IR LED Infrared Red Illuminator (GWIR100)
- 12 pcs of strong powered IR LED. Merit Li-Lin PRH-5218. IP 67 High efficiency infrared LED, radiant distance - 100 meter

Camera Mount



Adjustable Security Camera bracket (GWBR101)
- Adjustable Security Camera brackets, gray metal color, great for indoor/outdoor mounting. For bigger and heavier cameras



Security Camera bracket (GWBR100)
- Security Camera bracket, Sturdy Metal Mount, Can Be Used Indoor Or Outdoor, Great For Large Size Cameras And Outdoor Housing Cameras

LCD Mount & Bracket



10-26" LCD Monitor Wall-Mount Bracket (GW-E1026)



LCD Flat Panel Wall Mount Bracket (GWLCD401)
- LCD Flat Panel Wall Mount. Supports up to 66lbs (30kg) maximum. For LCD panel from 10 inch - 30 inch (25-74cm) maximum



14-37" LCD Monitor Wall-Mount Bracket (GW-E1437)



21-37" LCD Monitor Wall-Mount Bracket (GW-E2137)



14-37" LCD Monitor Ceiling Mount Bracket (GW-E1438)



36-65" LCD Monitor Wall-Mount Bracket (GW-E3665)



21-37" LCD Monitor Mount Bracket (GW-E2337)



36-63" LCD Monitor Ceiling Mount Bracket (GW-E3663)

Connector



BNC Female to BNC Female (GW1064)
- PACK OF 10



BNC Female to RCA Female (GW1098)
- PACK OF 10



BNC Female to RCA Male (GW1099)
- PACK OF 10



RCA Male to Male Connector (GW16079)
- PACK OF 10



RCA Female to RCA Female (GW16082)
- PACK OF 10



BNC Twist On (GW10009)
- PACK OF 10



BNC 2 Piece Crimp On (GW1002)
- PACK OF 10



BNC Connector Male to Male (GW1063)
- PACK OF 10



BNC T-shaped Connector, (1) Male to (2) Female (GW1071)
- PACK OF 10



BNC Male to F-Type Female (GW1084)
- PACK OF 10



BNC Male to RCA Female (GW1003)
- PACK OF 10



BNC Male to RCA Male (GW1083)
- PACK OF 10



2.1mm DC Jack Adaptor Connector (GW118)
- PACK OF 10

Video Balun



Video Balun (GW401F)

- Transmitting CCTV Video at distance up to 2000ft through CAT5 cable. Easy installation, and support most video device



Video Balun (GW402)

- Transmitting CCTV Video at distance up to 2000ft through CAT5 cable. Easy installation, and support most video device



Video Balun (GW401)

- Transmitting CCTV Video at distance up to 2000ft through CAT5 cable. Easy installation, and support most video device



Video & Audio Balun (GW403)

- Video & Audio Balun: Transmitting CCTV Video & Audio through CAT5 cable. Easy installation



4CH Passive UTP Video Balun (GW404A)

- Simultaneously transmit four channels of video signal through CAT5 twisted pair cable. Easy installation, and support most video device



4CH Passive UTP Video Balun (GW404C)

- Simultaneously transmit four channels of video signal through CAT5 twisted pair cable. Easy installation, and support most video device



8CH Passive UTP Video Balun (GW408P)

- Simultaneously transmit four channels of video signal through CAT5 twisted pair cable. Easy installation, and support most video device



16CH Passive UTP Video Balun (GW416P)

- Simultaneously transmit four channels of video signal through CAT5 twisted pair cable. Easy installation, and support most video device



32CH Passive UTP Video Balun (GW432P)

- Simultaneously transmit four channels of video signal through CAT5 twisted pair cable. Easy installation, and support most video device

Converter



AV-TO-VGA Converter (GWVGA210)

- Convert AV to VGA
- Resolving capability can be easily among (800 x 600, 1024 x 768, 1280 x 1024, 1440 x 900, 1680 x 1050, 1920x1080, 1920 x 1200), CRT MONITOR and LCD MONITOR are compatible

Microphone



Microphone for DVR (GWMICBA10)

- One add-on mini audio box for all Camera which need audio function
- High Sensitive microphone and 12V power regulator built-in box

Security Signs



Security Sign (GWSTICKER)

- Sticker



Security Sign (GWLA06)

- 9"x11"



Security Sign (GWLA05)

- 18"x12"



3.15" x 3.15" Plastic Warning Solar Flash CCTV Signboard (GWLA07)

- No battery needed. Solar cell operation
- Constantly blinking messages on the LCD
- Perfectly molded.

Test Monitor



- 2.5" TFT LCD test monitor (GW100LCD)**
- 2.4GHz Wireless Palm Monitor
 - 2.5" TFT LCD Display
 - Resolution: 480 x 234
 - 4-channel operation allows multiple (1-4) camera system



- 2.5" Wrist LCD Watch Test Monitor (GWT250)**
- LCD Watch Test Monitor with OSD Function
 - 2.5" TFT LCD Screen
 - OSD Menu
 - Power: AAA Battery X 6
 - NTSC / PAL Auto Recognition



- Portable 3.5" LCD Tester (GW-C80)**
- OSD menu
 - Portable, 3.5" LCD Monitor
 - Built-In 0.5W Buzzer
 - Lithium Battery (Charger Included)



- 3.5" TFT/LCD test monitor (GW35TM)**
- NEW LCD Monitor 3.5" TFT/LCD High Resolution Color Monitor w/ Battery Pack. DC12V 300mA. Great for professional installer, testing, and monitoring camera before lockup the camera view



- Multifunction CCTV tester (GW-MT200)**
- Test & Troubleshoot CCTV Cameras on the go
 - Easy to read 2.5" inch LCD Display
 - User friendly OSD menu
 - PTZ protocol analyzer that supports most PTZ protocols
 - High capacity Li-ion battery (Up to 5 hours)



- PTZ & Network Cable Tester (GW-MT250)**
- OSD menu; Network Cable Test, PTZ Control
 - Multi-Protocol Baud rate built-in
 - Auto Reduce Power Consumption up to 10 hours battery life
 - Up to 4 hours power supply for camera
 - RS232, RS422 & RS485 Synchronically



- Multifunction Security Tester with 3.5 inch TFL screen (GW3000)**
- Handheld 3.5 inch TFT high DPI monitor
 - Automatic identification of multi-system
 - OSD menu for product functions
 - Various ball machine control protocol and baud rate
 - Support 0~255 address



- Multifunction Security Tester with 3.5 inch TFL screen (GWT350)**
- High Quality 3.5" Color TFT Display, Brightness Adjustable
 - Hands Free, Adjustable neck, wrist straps
 - External Power Supply or Internal Rechargeable Battery, Stand By Up to 5~6hrs
 - On Screen Data Display

LCD Monitor



19" LCD Flat Panel Display Monitor (GWLCD19IN)

- LCD Flat Panel Display Monitor To Connect To Your DVR, For Better Resolution Than Your Traditional TV. Saves Space. 19 Inch. Comes With VGA Cable And Power Supply



19" Professional TFT LCD for surveillance (GWLCD1947)

- Professional TFT LCD for surveillance
- Compatible with VGA(640X480), SVGA(800X600), XGA(1024X768), SXGA(1280X1024) resolution
- Video input BNC x 1 / VGA x 1 / S-Video x 1
- Video output BNC x 1
- Audio input RCA x 2 / phone jack x 1

Wireless Baby Monitor



Professional 2.4 GHz Wireless Baby Monitor (GWDWBM4)

- 2.4" TFT LCD
- Two-way speak
- 380 TV Lines
- Transmission information is protected



Professional 2.4 GHz Wireless Baby Monitor (GWDWBM2)

- 2.4" TFT LCD
- Two-way speak
- 380 TV Lines
- Transmission information is protected



Professional 2.4 GHz Wireless Baby Monitor (GWDWBM1)

- 2.4" TFT LCD
- Two-way speak
- 380 TV Lines
- Transmission information is protected



Professional 2.4 GHz Wireless Baby Monitor (GWDWBM3)

- 2.5" TFT LCD
- Resolution: 480x234
- 380 TV Lines
- Built-in Speaker